



Raccordo maschio

- Installazione senza disassemblaggio
- Idoneo per tubi in PE e PEX
- Acqua PN16
- Materiale: PP
- Guarnizione: NBR per acqua potabile
- Filetto maschio: ISO 7 (conico)
- Colore: azzurro-nero

d	R	PN	Codice	SP	GP	Peso	D	L	l1	l2	l3
(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
16	½	16	158 400 351	1	75	0,037	45	73	46	19	14
16	¾	16	158 400 352	1	75	0,040	51	74	46	19	14
20	½	16	158 400 123	1	220	0,037	45	73	54	19	14
20	¾	16	158 400 124	1	220	0,040	45	74	54	19	15
20	1	16	158 400 125	1	220	0,038	45	77	54	19	17
25	½	16	158 400 126	1	180	0,050	53	79	59	21	14
25	¾	16	158 400 127	1	180	0,056	53	80	59	21	15
25	1	16	158 400 128	1	170	0,057	53	83	59	21	17
32	¾	16	158 400 129	1	120	0,088	64	88	66	23	15
32	1	16	158 400 130	1	120	0,091	64	91	66	23	17
32	1 ¼	16	158 400 131	1	120	0,092	64	93	66	23	20
32	1 ½	16	158 400 132	1	115	0,098	64	93	66	23	20
40	1	16	158 400 133	90	0	0,136	75	102	76	26	17
40	1 ¼	16	158 400 134	90	0	0,153	75	104	76	26	20
40	1 ½	16	158 400 135	90	0	0,142	75	104	76	26	20
40	2	16	158 400 136	80	0	0,154	75	109	76	26	24
50	1	16	158 400 137	50	0	0,265	97	114	88	30	17
50	1 ¼	16	158 400 138	50	0	0,267	97	117	88	30	20
50	1 ½	16	158 400 139	50	0	0,247	97	117	88	30	20
50	2	16	158 400 140	50	0	0,273	97	121	88	30	24
63	1 ½	16	158 400 141	30	0	0,421	114	135	104	35	20
63	2	16	158 400 142	30	0	0,437	114	139	104	35	24
63	2 ½	16	158 400 143	25	0	0,427	114	143	104	35	28
75	2	16	158 400 144	18	0	0,768	135	170	133	41	24
75	2 ½	16	158 400 145	18	0	0,763	135	174	133	41	28
75	3	16	158 400 146	18	0	0,791	135	177	133	41	30
90	2	16	158 400 147	8	0	1,225	161	189	150	44	24
90	2 ½	16	158 400 148	8	0	1,139	161	193	150	44	28
90	3	16	158 400 149	8	0	1,144	161	196	150	44	30
90	4	16	158 400 150	8	0	1,201	161	202	150	44	36
110	3	16	158 400 151	6	0	1,831	185	222	175	53	30
110	4	16	158 400 152	6	0	1,854	185	228	175	53	36